

# Declaration of Performance



No. 1105-S,1126-S

- 1 Unique identification code of the product type Lithurin Seal
- 2 Intended use/es EN 1504-2:  
Protection against Ingress – impregnation (1.2)  
Physical resistance/Surface Improvement – impregnation (5.2)
- 3 Manufacturer AB Lindec  
Address: Box 5, 421 21 Västra Frölunda, Sweden  
Telephone: +46 31-29 88 10  
Telefax: +46 31-29 88 76  
E-mail: info@lindec.se
- 4 Authorised representative Not relevant
- 5 System/s of AVCP EN 1504-2:  
System 4 (for uses with low performance requirements in buildings and civil engineering works)  
System 4 for fire behaviour (for uses subject to reaction to fire regulations)
- 6a Harmonised standard EN 1504-2:2004 (ZA.1b, ZA.1c)  
Notified body Not relevant for system 4
- 6b European Assessment Document Not relevant  
European Technical Assessment Not relevant
- 7 Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Abrasion resistance/Water resistance	Class AR1	EN 13892-4
Capillary absorption and permeability to water	$> 0,1 \text{ kg/m}^2 \times \text{h}^{0,5}$	EN 1504-2:2004
Impact Resistance	$\geq 4 \text{ Nm}$ , Class 1	EN 1504-2:2004
Adhesion strength by pull off test	NPD	EN 1504-2:2004
Slip Resistance (Dry test)	104, Class II	EN 1504-2:2004
(Wet test)	42, Class I	EN 1504-2:2004
Reaction to fire	F	EN 1504-2:2004
Depth of penetration	Class I (< 10 mm)	EN 1504-2:2004

NPD = No performance determined

- 8 Appropriate Technical Documentation and/or Specific Technical Documentation Not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Gothenburg, 27.04.2015

Signed on behalf of the manufacturer by:

Mikael Voeler  
Managing Director

